

## PGK 50 E / PGK 80 E

### BAUR DC HV tester



The figure is illustrative.

### Small, lightweight and powerful

- Compact device for DC voltage testing with negative polarity
- Sensitive current measurement for recording extremely small insulation currents
- Easily portable thanks to practical case

The portable PGK 50 E and PGK 80 E DC HV testers are used for DC voltage testing up to 50 kV or 80 kV of paper-insulated mass-impregnated cables and electrical equipment in the medium-voltage network.

Sensitive current measurement permits the detection of extremely small insulation currents, which are used to determine insulation resistances up to the tera-ohm range. An external curve tracer can be connected to the PGK 50 E/PGK 80 E to record the measured current in relation to time.

The integrated discharge unit operates automatically and independently of the device situation, even in the event of power failure. A clear switching noise can be heard. The discharging resistance is designed for a max. discharge energy of 8000 J.

Thanks to their small dimensions and the practical case with carrying handle and carrying strap, the PGK 50 E and PGK 80 E are optimal for use on site.

#### Functions

- On-site testing of paper-insulated mass-impregnated cables according to:
  - IEEE 400-2012
  - IEC 60060-3
- Voltage test on electrical equipment according to:
  - IEEE 62.2
  - IEEE 95
- Cable sheath testing according to:
  - IEC 60502 / IEC 60229
  - VDE DIN 0276-620/621 (CENELEC HD 620/621)

#### Features


- Negative test voltages:
  - PGK 50 E: DC 0 – 50 kV
  - PGK 80 E: DC 0 – 80 kV
- Integrated timer (1-30 min) with automatic switch-off of the high voltage and triggering of the discharge unit
- Continuously adjustable output voltage
- Safety control unit according to EN 50191
- Ammeter with 6 measurement ranges from 1  $\mu$ A to 100 mA
- All connection elements and cables are in a robust case
- Short-circuit-proof design
- Connection for external emergency off unit, external door contact and signal lamps
- Connection for external curve tracer for recording the test current

### Technical data


Testing	PGK 50 E	PGK 80 E
DC voltage (negative)	0 – 50 kV	0 – 80 kV
Output current (negative)	2 mA @ 50 kV	0.8 mA @ 80 kV 1.5 mA @ 70 kV
Short-circuit current (negative)	25 mA	20 mA
Voltage measuring range		
Range I	0 – 50 kV	0 – 80 kV
Range II	0 – 10 kV	0 – 16 kV
Current measuring range	20 nA to 1 $\mu$ A / 10 $\mu$ A / 100 $\mu$ A / 1 mA / 10 mA / 100 mA	
Accuracy of the voltmeter (kV)	$\pm 2.5\%$	
Timer	0 – 30 min	
Max. discharge energy	8000 J at 1 discharge/15 min (ambient temperature 20°C)	

General	
Power supply	110/120 V, 220/230 V, 240 V, 50/60 Hz
Power consumption	<ul style="list-style-type: none"> <li>▪ PGK 50 E: 1 600 VA</li> <li>▪ PGK 80 E: 1 400 VA</li> </ul>
Degree of protection	IP53 (in closed state)
Ambient temperature (operational)	0°C to +45°C
Storage temperature	-20°C to +60°C
Relative humidity	Non-condensing
Dimensions (W x H x D)	Approx. 495 x 460 x 285 mm
Weight	Approx. 25 kg
Safety and EMC	CE-compliant in accordance with Low Voltage Directive (2014/35/EU), EMC Directive (2014/30/EU), EN 60068-2-ff Environmental testing

### PGK 50 E load diagram



### PGK 80 E load diagram



### Standard delivery

- BAUR PGK 50 E or PGK 80 E DC HV tester
- HV connection cable, 5 m, fix mounted
- Earth cable, 3 m, with earth terminal
- Operational earthing cable, 4 m, for current measurement
- Mains supply cord, 2.5 m
- User manual

### Option for PGK 50 E

- Discharge and earth rod GDR 60-375

### Option for PGK 80 E

- GDR 80-500 discharge and earth rod

### Contact:

BAUR GmbH (Head Office Austria)  
T +43 (0)5522 4941-0  
F +43 (0)5522 4941-3  
headoffice@baur.at  
[www.baur.eu](http://www.baur.eu)

BAUR Prüf- und Messtechnik GmbH  
T +49 (0)2181 2979 0  
F +49 (0)2181 2979 10  
vertrieb@baur-germany.de  
[www.baur-germany.eu](http://www.baur-germany.eu)

BAUR France  
T +33 (0) 170 701 045  
F +33 (0) 172 718 485  
info@baur-france.at  
[www.baur.eu/fr](http://www.baur.eu/fr)

Baur do Brasil Ltda.  
T +55 11 297 25 272  
atendimento@baurdobrasil.com.br  
[www.baurdobrasil.com.br](http://www.baurdobrasil.com.br)

奥地利保尔公司上海代表处  
电话 +86 (0)21 6133 1877  
传真 +86 (0)21 6133 1886  
shanghaioffice@baur.at  
[www.baur.eu/china](http://www.baur.eu/china)

BAUR Test Equipment Ltd. (UK)  
T +44 (0)20 8661 957  
sales@baurtest.com  
[www.baurtest.com](http://www.baurtest.com)

BAUR Representative Office Hong Kong  
T +852 2780 9029  
F +852 2780 9039  
office.hongkong@baur.at  
[www.baur.eu](http://www.baur.eu)

BAUR representatives:  
[www.baur.eu/en/baur-worldwide](http://www.baur.eu/en/baur-worldwide)